



TECTUL

Manguera para succión de aire

MATERIALES

APLICACIÓN

CARÁCTERÍSTICAS DIMENSIONALES



Características adicionales
Pared interna lisa para un flujo de aire óptimo y reducción de la fricción.
Puede operar en un rango de temperatura estándar.
Opciones de refuerzo con alambre de acero para aplicaciones de succión más pesadas.
Fabricada con materiales de alta calidad para una mayor durabilidad.

Datos técnicos						
Diámetro nominal - NPS [in]	Diámetro interior - Di [mm]	Diámetro exterior - De [mm]	Espesor de pared - t [mm]	W/P PSI	B/P PSI	Longitud de rollo [mtr]
1	25	32	3,5	60	180	60
1 1/4	32	40	4,0	60	180	60
1 1/2	38	46	4,0	50	150	60
2	51	60	4,5	50	150	45
2 1/2	64	73	4,5	40	120	45
3	76	86	5,0	40	120	30
4	102	113	5,5	40	120	30
5	127	139	6,0	40	120	30
6	152	166	7,0	30	90	30

MATERIALES
Fabricada en tubo suave termoplástico.

APLICACIÓN
Ideal para sistemas de ventilación, aspiradoras industriales, recolección de polvo y aplicaciones que requieren succión de aire.

CARÁCTERÍSTICAS DIMENSIONALES
Variaciones desde 1" a 6"

* Fotos y medidas referenciales, sujetas a cambios sin previo aviso por parte del proveedor o fabricante.



TECTUL

Air suction hose

APPLICATION



MATERIALS



DIMENSIONAL CHARACTERISTICS



Additional Features
Smooth inner wall for optimal airflow and reduced friction.
Can operate within a standard temperature range.
Options for steel wire reinforcement for heavier suction applications.
Manufactured from high-quality materials for enhanced durability.

Mechanical data						
Nominal diameter - NPS [in]	Internal diameter - Di [mm]	External diameter - De [mm]	Wall thickness - t [mm]	W/P PSI	B/P PSI	Roll length [mtr]
1	25	32	3,5	60	180	60
1 1/4	32	40	4,0	60	180	60
1 1/2	38	46	4,0	50	150	60
2	51	60	4,5	50	150	45
2 1/2	64	73	4,5	40	120	45
3	76	86	5,0	40	120	30
4	102	113	5,5	40	120	30
5	127	139	6,0	40	120	30
6	152	166	7,0	30	90	30



MATERIALS

Made of soft thermoplastic tube.



APPLICATION

Ideal for ventilation systems, industrial vacuum cleaners, dust collection, and applications that require air suction.



DIMENSIONAL CHARACTERISTICS

Variations from 1" to 6"

* Reference photos and measurements, subject to change without prior notice from the supplier or manufacturer.