



TECTUL

Manguera Transparente Espiral Acero

APLICACIÓN



MATERIALES



CARÁCTERÍSTICAS DIMENSIONALES



Datos técnicos							
Nominal [in]	DI mm	De mm	Espesor de Pared mm	W/P psi/BAR	B/P psi/BAR	Peso Aprox [Kg]	Longitud de Rollo [m]
3/8	9	15	3,0	160	480	18	100
1/2	12	18	3,0	145	435	22	100
5/8	15	22	3,5	145	435	31	50
3/4	19	26	3,5	145	435	19	50
7/8	22	29	3,5	120	360	24	50
1	25	33	4,0	100	300	27,5	50
1-1/4	32	41	4,5	100	300	31,6	50
1-1/2	38	48	5,0	85	255	40,5	50
2	50	62	6,0	70	210	63	50
2-1/2	63	80	8,5	65	195	57,5	50
3	75	92	8,5	60	180	66,8	30
4	100	100	9,0	45	135	93	30

MATERIALES



Manguera sanitaria transparente con espiral de acero.

APLICACIÓN



Utilizada en bombas de vacío, agricultura, industria química, equipos sanitarios, alimentos y procesamiento de plástico.

CARÁCTERÍSTICAS DIMENSIONALES



Medidas varían de 3/8" a 4".
Presentación por rollos de 30 a 100 metros.

Características adicionales

Resistencia a la abrasión.
Excelente resistencia química.
Temperatura de trabajo de 60°C.

* Fotos y medidas referenciales, sujetas a cambios sin previo aviso por parte del proveedor o fabricante.



TECTUL

Transparent Hose with Steel Spiral

APPLICATION



MATERIALS



DIMENSIONAL CHARACTERISTICS



Technical Data							
Nominal [in]	DI mm	DE mm	Wall Thickness mm	W/P psi/BAR	B/P psi/BAR	Aprox Weight [Kg]	Roll Length [m]
3/8	9	15	3,0	160	480	18	100
1/2	12	18	3,0	145	435	22	100
5/8	15	22	3,5	145	435	31	50
3/4	19	26	3,5	145	435	19	50
7/8	22	29	3,5	120	360	24	50
1	25	33	4,0	100	300	27,5	50
1-1/4	32	41	4,5	100	300	31,6	50
1-1/2	38	48	5,0	85	255	40,5	50
2	50	62	6,0	70	210	63	50
2-1/2	63	80	8,5	65	195	57,5	50
3	75	92	8,5	60	180	66,8	30
4	100	100	9,0	45	135	93	30



MATERIALS

Transparent sanitary hose with steel spiral.



APPLICATION

Used in vacuum pumps, agriculture, chemical industry, sanitary equipment, food and plastic processing.



DIMENSIONAL CHARACTERISTICS

Measurements vary from 3/8" to 4". Presentation in rolls of 30 to 100 meters.

Additional characteristics

Abrasion resistance.
Excellent chemical resistance.
Working temperature of 60°C.

* Reference photos and measurements, subject to change without prior notice from the supplier or manufacturer.