



TECTUL

Manguera Para Limpieza De Alcantarilla

MATERIALES



CARÁCTERÍSTICAS DIMENSIONALES



APLICACIÓN



Datos técnicos							
Nominal [in]	DI mm	De mm	W/P psi/BAR	B/P psi/BAR	Elongación	Rad. Curv. Min. Mm	Peso Aprox.
1/2	13,0	22,5	2900/200	7250/500	+/-1,5%	80	290
5/8	16,4	25,0	2900/200	7250/500	+/-1,5%	90	350
3/4	19,5	31,0	2900/200	7250/500	+/-1,5%	100	480
1	25,2	38,5	2900/200	7250/500	+/-1,5%	150	714
1-1/4	32,5	48,5	2900/200	7250/500	+/-1,5%	200	1010

MATERIALES



Tubo interior de polietileno.
Refuerzo textil de alta tensión.
Cubierta de poliuretano.

APLICACIÓN



Usado para la limpieza en alcantarillas.

CARÁCTERÍSTICAS DIMENSIONALES



Medidas varían de 1/2" a 1-1/4".
Presentación por rollo de 100 metros.

Características adicionales

Temperatura: -20°C a +40°C.
Factor de seguridad: 1:2,5.
Cubierta resistente a la abrasión, cortes y hongos.
Ideal para montar en camiones tipo vector.
Presión de trabajo de 2900 psi.

* Fotos y medidas referenciales, sujetas a cambios sin previo aviso por parte del proveedor o fabricante.



TECTUL

Sewer Cleaning Hose

APPLICATION



MATERIALS



DIMENSIONAL CHARACTERISTICS



Technical Data							
Nominal [in]	DI mm	DE mm	W/P psi/BAR	B/P psi/BAR	Elongation	Min. Curv. Rad. mm	Aprox. Weight
1/2	13,0	22,5	2900/200	7250/500	+/-1,5%	80	290
5/8	16,4	25,0	2900/200	7250/500	+/-1,5%	90	350
3/4	19,5	31,0	2900/200	7250/500	+/-1,5%	100	480
1	25,2	38,5	2900/200	7250/500	+/-1,5%	150	714
1-1/4	32,5	48,5	2900/200	7250/500	+/-1,5%	200	1010

Additional characteristics

Temperature: -20°C to +40°C.

Safety factor: 1:2.5.

Abrasion, cut and fungus resistant cover.

Ideal for mounting on vector type trucks.

Working pressure of 2900 psi.

MATERIALS



Polyethylene inner tube.
High tension textile reinforcement.
Polyurethane cover.

APPLICATION



Used for cleaning sewers.

DIMENSIONAL CHARACTERISTICS



Measurements vary from 1/2" to 1-1/4".
Presentation per roll of 100 meters.

* Reference photos and measurements, subject to change without prior notice from the supplier or manufacturer.