



TECTUL

VÁLVULA NEUMÁTICA RODILLO 3-2

CARACTERÍSTICAS

APLICACIONES

MATERIALES



CARACTERÍSTICAS

Válvula neumática de accionamiento mecánico por rodillo, tres vías, dos posiciones.

MATERIALES

Cuerpo de aluminio, sellos de NBR

APLICACIONES

Utilizada para controlar pilotos o diafragmas de válvulas más grandes o cilindros pequeños

DATOS TÉCNICOS

ATRIBUTO	DESCRIPCIÓN
Tipo de Válvula	Válvula neumática tipo rodillo 3-2
Cuerpo	Aluminio
Asiento	NBR
Extremos	Rosca NPT
Operación	Rodillo
Clase PSIG	114 PSI
Característica	Sin enclavamiento
Limites de temperatura	0°C A 70°C

* Fotos y medidas referenciales, sujetas a cambios sin previo aviso por parte del proveedor o fabricante.



TECTUL

PNEUMATIC ROLLER VALVE 3-2

CHARACTERISTICS

APPLICATIONS

MATERIALS



CHARACTERISTICS

Actuating pneumatic valve mechanical by roller, three ways, two positions.



MATERIALS

Aluminum body, NBR seals



APPLICATIONS

Used to control pilots or larger valve diaphragms or small cylinders

TECNICAL DATA

ATTRIBUTE	DESCRIPTION
Valve Type	Roller Type Pneumatic Valve 3-2
Body	Aluminum
Seat	NBR
Extremes	NPT thread
Operation	Roller
PSIG class	114 psi
Characteristic	Non-locking
Temperature limits	0 °C to 70 °C

* Reference photos and measurements, subject to change without prior notice from the supplier or manufacturer.