



TECTUL

PASAMURO PRESTOLOK

CARACTERÍSTICAS

APLICACIONES



MATERIALES



* Vista de sección transversal de tipo informativa. No representa versión específica del accesorio.

CARACTERÍSTICAS



Ideales para conexiones neumáticas, Permite realizar una conexión y desconexión de forma inmediata.

MATERIALES



Latón niquelado (rosca) y PBT (cuerpo).

APLICACIONES



Utilizados en el transporte de fluidos como el aire, el gas, el aceite y el agua.

DATOS TÉCNICOS

DIÁMETRO	L [mm]	PESO [g]
12mm	45.00*	66.00*
10mm	42.00*	52.00*
8mm	35.00*	26.00*
6mm	31.30*	21.00*
1/2"	45.50*	61.00*
3/8"	44.00*	55.00*
1/4"	31.00*	20.00*

* Fotos y medidas referenciales, sujetas a cambios sin previo aviso por parte del proveedor o fabricante.



TECTUL

PRESTOLOK GROMMET

CHARACTERISTICS

APPLICATIONS



MATERIALS



* Informational type cross section view. It does not represent the specific version of the accessory.

CHARACTERISTICS



Ideal for pneumatic connections,
Allows you to connect and
immediate disconnection.

MATERIALS



Nickel-plated brass (thread)
and PBT (body).

APPLICATIONS



Used in the transport of fluids
such as air, gas, oil and water.

TECNICAL DATA

MEASURE	L [mm]	WEIGHT [g]
12mm	45.00*	66.00*
10mm	42.00*	52.00*
8mm	35.00*	26.00*
6mm	31.30*	21.00*
1/2"	45.50*	61.00*
3/8"	44.00*	55.00*
1/4"	31.00*	20.00*

* Reference photos and measurements, subject to change without prior notice from the supplier or manufacturer.