



TECTUL

UNIÓN PRESTOLOK

CARACTERÍSTICAS

APLICACIONES



MATERIALES



* Vista de sección transversal de tipo informativa. No representa versión específica del accesorio.

CARACTERÍSTICAS



Ideales para conexiones neumáticas, Permite realizar una conexión y desconexión de forma inmediata.

MATERIALES



Latón niquelado (rosca) y PBT (cuerpo).

APLICACIONES



Utilizados en el transporte de fluidos como el aire, el gas, el aceite y el agua.

DATOS TÉCNICOS

DIÁMETRO	L [mm]	PESO [g]
12mm	48.80*	16.00*
10mm	47.00*	13.00*
8mm	39.00*	8.00*
6mm	35.60*	5.00*
4mm	33.40*	4.00*
1/2"	48.50*	16.00*
1/4"	36.00*	5.00*
5/16"	39.00*	7.00*
3/8"	47.00*	13.00*
1/8"	33.50*	4.00*

* Fotos y medidas referenciales, sujetas a cambios sin previo aviso por parte del proveedor o fabricante.



TECTUL

PRESTOLOK UNION

CHARACTERISTICS

APPLICATIONS

MATERIALS



* Informational type cross section view. It does not represent the specific version of the accessory.

CHARACTERISTICS



Ideal for pneumatic connections,
Allows you to connect and
immediate disconnection.

MATERIALS



Nickel-plated brass (thread)
and PBT (body).

APPLICATIONS



Used in the transport of fluids
such as air, gas, oil and water.

TECNICAL DATA

MEASURE	L [mm]	WEIGHT [g]
12mm	48.80*	16.00*
10mm	47.00*	13.00*
8mm	39.00*	8.00*
6mm	35.60*	5.00*
4mm	33.40*	4.00*
1/2"	48.50*	16.00*
1/4"	36.00*	5.00*
5/16"	39.00*	7.00*
3/8"	47.00*	13.00*
1/8"	33.50*	4.00*

* Reference photos and measurements, subject to change without prior notice from the supplier or manufacturer.