



TECTUL

CODO PRESTOLOK

CARACTERÍSTICAS

APLICACIONES

MATERIALES



* Vista de sección transversal de tipo informativa. No representa version especifica del accesorio.

DATOS TÉCNICOS		
DIÁMETRO	M [mm]	PESO [g]
12mm	36.00*	18.00*
10mm	34.70*	16.00*
8mm	28.00*	7.00*
6mm	23.50*	5.00*
4mm	17.10*	4.00*
1/2"	36.70*	18.00*
1/4"	23.40*	5.00*
5/16"	22.50*	7.30*
3/8"	33.60*	14.00*
1/8"	20.70*	4.00*

* Fotos y medidas referenciales, sujetas a cambios sin previo aviso por parte del proveedor o fabricante.



CARACTERÍSTICAS

Ideales para conexiones neumáticas, Permite realizar una conexión y desconexión de forma inmediata.



MATERIALES

Latón niquelado (rosca) y PBT (cuerpo).



APLICACIONES

Utilizados en el transporte de fluidos como el aire, el gas, el aceite y el agua.



TECTUL

PRESTOLOK ELBOW

CHARACTERISTICS

APPLICATIONS



MATERIALS



* Informational type cross section view. It does not represent the specific version of the accessory.

CHARACTERISTICS



Ideal for pneumatic connections,
Allows you to connect and
immediate disconnection.

MATERIALS



Nickel-plated brass (thread)
and PBT (body).

APPLICATIONS



Used in the transport of fluids
such as air, gas, oil and water.

TECNICAL DATA

MEASURE	L [mm]	WEIGHT [g]
12mm	36.00*	18.00*
10mm	34.70*	16.00*
8mm	28.00*	7.00*
6mm	23.50*	5.00*
4mm	17.10*	4.00*
1/2"	36.70*	18.00*
1/4"	23.40*	5.00*
5/16"	22.50*	7.30*
3/8"	33.60*	14.00*
1/8"	20.70*	4.00*

* Reference photos and measurements, subject to change without prior notice from the supplier or manufacturer.