



TECTUL

TEE PRESTOLOK

CARACTERÍSTICAS

APLICACIONES



MATERIALES



* Vista de sección transversal de tipo informativa. No representa versión específica del accesorio.

CARACTERÍSTICAS



Ideales para conexiones neumáticas, Permite realizar una conexión y desconexión de forma inmediata.

MATERIALES



Latón niquelado (rosca) y PBT (cuerpo).

APLICACIONES



Utilizados en el transporte de fluidos como el aire, el gas, el aceite y el agua.

DATOS TÉCNICOS

DIÁMETRO	M [mm]	PESO [g]
1/8"	18.50*	6.00*
1/4"	20.75*	8.00*
5/16"	22.35*	11.00*
3/8"	26.00*	19.00*
1/2"	29.40*	27.00*
12mm	29.40*	28.00*
10mm	26.00*	19.00*
8mm	23.00*	11.00*
6mm	19.35*	8.00*
4mm	17.10*	5.00*

* Fotos y medidas referenciales, sujetas a cambios sin previo aviso por parte del proveedor o fabricante.



TECTUL

TEE PRESTOLOK

CHARACTERISTICS

APPLICATIONS

MATERIALS



* Informational type cross section view. It does not represent the specific version of the accessory.

CHARACTERISTICS



Ideal for pneumatic connections,
Allows you to connect and
immediate disconnection.

MATERIALS



Nickel-plated brass (thread)
and PBT (body).

APPLICATIONS



Used in the transport of fluids
such as air, gas, oil and water.

TECNICAL DATA

MEASURE	M [mm]	WEIGHT [g]
1/8"	18.50*	6.00*
1/4"	20.75*	8.00*
5/16"	22.35*	11.00*
3/8"	26.00*	19.00*
1/2"	29.40*	27.00*
12mm	29.40*	28.00*
10mm	26.00*	19.00*
8mm	23.00*	11.00*
6mm	19.35*	8.00*
4mm	17.10*	5.00*

* Reference photos and measurements, subject to change without prior notice from the supplier or manufacturer.